

EcoLift™ SERIES

NON-POWERED VERTICAL LIFTS



Performance

	EcoLift 50	EcoLift 70
Working Height	10 ft 11 in. (3.33 m)	13 ft 2.5 in (4.03 m)
Platform Height	4 ft 11 in. (1.50 m)	7 ft 2.5 in (2.20 m)
Stowed Height	5 ft 1 in. (1.55 m)	6 ft 4 in. (1.94 m)
Stowed Width	27.5 in. (0.7 m)	27.5 in. (0.7 m)
Stowed Length	3 ft 2.7 in. (0.985 m)	4 ft 2.3 in. (1.28 m)
Platform Size	28 x 23.6 in. (72 x 60 cm)	33.4 x 25.4 in. (85 x 64.4 cm)
Rated Capacity	330 lb (150 kg)	330 lb (150 kg)
Weight	397 lb (180 kg)	672 lb (305 kg)

Standard Features

- Unlimited lift cycles
- Rust-free aluminum platform w/diamond tread
- Full-height self-closing saloon gate
- Tool tray
- Frame-mounted bubble level
- Protective wall bumpers
- Integrated fork pockets
- Auto-braked when entering platform
- Auto-locking brakes on elevation
- Mechanically detented handle

Applications

- Commercial and residential painting
- Facility maintenance
- Displays and decorating
- HVAC maintenance
- Retail retrofit
- Interior finish work
- Renovations and remodeling
- Plant maintenance
- Equipment installers — cable, security, audio-visual



Non-powered **EcoLift™** vertical lifts are an eco-friendly alternative to your powered access needs. They are hydraulic oil and battery free. And with no need to charge the **EcoLift™** Series has no energy consumption.



The JLG "1 & 5" Warranty

We provide coverage for one (1) full year, and cover all specified major structural components for five (5) years. Due to continuous product improvements, we reserve the right to make specification and/or equipment changes without prior notification. This machine meets or exceeds applicable ANSI and CSA requirements based on machine configuration as originally manufactured for intended applications. Please reference the serial number plate on the machine for additional information.

Part No.: 3132134
R061804
Printed in USA