



# HYTOWER

TRAK LIFTS

## MS-44





## MS-44



# HYTOWER TRAK LIFTS

## Power

9.5 Hp Gas	.4 mph Slow / .7 mph Fast
120V AC	.2 mph

## Travel Speed

## Standard Features

Remote Control Operation	120V Electrical Motor	Automatic Basket Leveling
Automatic Outrigger Stabilization	All Motion Alarm	Basket Access Ladder
Proportional Full Hydraulic Controls	Hour Meter	2 Harness Attach Points
Non-Marking Rubber Tracks	4 Outriggers	Emergency Descent Pump
Cylinder Lock Valves	Emergency Controls at Ground Station	120V Power to Platform

## Performance

Max. Working Height	44'
Max. Platform Height	37' 6"
Max. Basket Capacity	440 lbs
Turret Rotation	360° (+180° / -180°)
Max. Horizontal Outreach	21' 4"
Up & Over Clearance	14' 9"
Max. Gradeability	30%
Max. Angle of Approach	17°
Max Slope Angle for Stabilization	6°
Length	10' 4"
Width With Basket	3' 7"
Width Without Basket	2' 9"
Height	7' 2"
Outrigger Footprint Length	11' 3"
Outrigger Footprint Width	11' 11"
Track Length	3' 4"
Track Width	10"
Weight	3,615 lbs

